

# Python – Programming Assignment 7

---

Professor:

Dr. Joanna Bieri  
joanna\_bieri@redlands.edu

---

**Directions:** Write a function that tracks pet feedings. The function should compute different results depending on a mode parameter.

---

Specifications:

- Write a function called `feeding_tracker(feedings, mode)`.
- The function should accept two parameters.
  - The first parameter is a dictionary where the **keys** are pet names and the **values** are lists of numbers representing how much food (in cups) the pet ate at each feeding.
  - The second parameter is a string that can be one of the following values: `total`, `avg`, `most`, `least`, or `none`. The default value should be `total`.
    - \* If the parameter is “total,” print the **total food eaten for each pet** and return a dictionary of totals.
    - \* If it is “avg,” print the **average amount eaten per feeding** for each pet.
    - \* If it is “most,” print the **largest feeding amount** for each pet.
    - \* If it is “least,” print the **smallest feeding amount** for each pet.
    - \* If it is “none,” print a message and return the original dictionary unchanged.
    - \* If it is any other value, print an error message and return the original data.
- EXTRA CHALLENGE: Do **not** use the built-in Python functions `sum()`, `max()`, or `min()`. Instead write your own helper functions (for example `my_max()`, `my_min()`) using loops and comparisons.
- Example for testing:

```
feedings = { 'Bella' : [0.5, 1.0, 0.75, 1.25, 0.5] }
```

```
feeding_tracker(feedings,'total')
```

should print:

Bella ate a total of 4.0 cups!

and return:

```
{'Bella': 4.0}
```

If we use an invalid mode like:

```
feeding_tracker(feedings,'banana')
```

the program should print an error and return:

```
{ 'Bella' : [0.5, 1.0, 0.75, 1.25, 0.5] }
```

Try your program with multiple pets!